



Wallscape Dry Erase Wallcovering
Printed / Non-Woven Backing / Snow White Base Colorway
Specification: LOW-GLOSS-NW1051PDE

PHYSICAL PROPERTIES

Face Content.....100% Vinyl / Clear matt coated
UV Non Solvent Based Print Pigment.....09ppb
Type II.....20 ounce
Width.....50 inches
Backing.....Non-Woven Cellulose
Recycle Properties.....100% Recyclable
Pattern Repeat.....Image sensitive

FEDERAL SPECIFICATIONS

Class A Fire Rated

Test #3945-0556

ASTM E-84 Tunnel Test

Report 07-11030

Smoke Developed Index.....35
Flame Spread Index.....25
Light Fastness.....100 Hours no change
Maintenance / Mild soap warm water to maintain, 75% Alcohol with soft cloth for permanent/marker removal.

New York City Buildings Department MEA Compliant

The Flame Spread Rating indicated should not be construed to indicate hazards present under actual fire conditions. As such it does not release, or otherwise result in exposure to a hazardous chemical under normal conditions of use. This product is projected for use in buildings that are suitably designed and maintained to avoid moisture permeation, condensation and or accumulation at wall cavities and wall surfaces, particularly in humid climates. Do not install any wallcovering if the walls appear to have moisture damage. Walls shall not contain more than 5% of moisture content. If you are unsure if moisture damage has occurred please consult a professional before proceeding. Applications must follow Wallscape installation guidelines.

All wallcovering products are sold and subject to Wallscape 10 year Limited and Exclusive Warranty.