



MATERIAL SAFETY DATA SHEET

Manufacturer/s Name: Wallscape Wallcovering F.O.B. 646 Route 18 East Brunswick New Jersey 08816

Product model number call 1.866.216.4483

Email info@wallscapeinc.com

Emergency contact Infotrac (24 hour) 800-535-5053

Section 1:

Chemical Name and Synonyms:
Proprietary Composite Laminate
Trade Name and Synonyms:
Erasable Wallcovering Chemical Family: Blend of Polymers &
fillers Chemical Formula: N/A

Erasable Wallcovering,
Matt finish non-woven backing, print receptive surface

Sections 2-7

Section II

Hazardous Ingredients This composite contains negligible or trace quantities of VOCs (Volatile Organic Compound). Ingredients PEL (mg/m³) TLV (mg/m³) % Barium Compounds* ---- 0.5 0-3 Zinc Compounds* ---- 0.5 0-3 PEL's and TLV's indicated are for parent metals of metal compounds. (*) – Indicated a compound category subject to SARA Section 313 reporting over 5%

Section III

Physical Data Boiling Point (F°) N/A Specific Gravity (H₂O=1) 1.28 – 1.60 Vapor Pressure (MM Hg) N/A Percent, Volatile by Volume (%) < 1% Vapor Density (Air=1) N/A Evaporation Rate (= 1) N/A Solubility in Water Very Slight Decomposition Temperature > 400°F Appearance and Odor: Glossy white appearance, very mild odor

Section IV

Fire and Explosion Hazard Data Flash Point: N/A Flammable Limits N/A LEL UEL Extinguishing Media: Dry Chemical, Foam, and CO₂ Special Fire Fighting Procedures: Wear NIOSH Approved Self-Contained Breathing apparatus and preventive clothing to prevent contact with skin and eyes. Unusual Fire and Explosion Hazards : Decomposition by burning in open flame produces toxic Hydrogen Chloride gas (HCl), Carbon Dioxide (CO₂), Carbon Monoxide (CO), and residual vinyl chloride monomers (See Section V – Health Hazard Data and Section VI – Reactivity Data).

Section V

Health Hazard Data Primary Routes of Exposure: INHALATION: Dusts may irritate the respiratory tract. EYES: Dusts may irritate eyes. Injury to eye tissue will occur under conditions of prolonged contact. SKIN: Dusts may irritate and dry the skin. Plasticizers may be absorbed through the skin. INGESTION: Not a likely route of exposure. Emergency and First Aid Procedures: INHALATION: If affected, remove to fresh air. If breathing is difficult administer oxygen. If breathing has stopped give artificial respiration and seek medical attention immediately. EYES: Flush with large amounts of water, lifting upper and lower lids occasionally. Get medical attention if irritation persists. SKIN: Thoroughly wash exposed area with soap and water. If irritation or rash develops get medical attention. Remove contaminated clothing and launder before re-use. INGESTION: Give plenty of water. Consult with physician.

Section VI

Reactivity Data Stability Unstable Conditions to avoid: Stable X Incompatibility (Material to Avoid): Avoid contact with Organic acids, Chlorinated Hydrocarbons and aromatic solvents which may cause softening and swelling of the film. Hazardous Decomposition Products: Hydrogen Chloride (HCL), Carbon Dioxide (CO₂), Carbon Monoxide (CO), residual monomers. Hazardous Polymerization May Occur Conditions to avoid: Will not Occur X

Section VII

Spill or Leak Procedures Steps to be taken in case material is released or spilled: N / A

Waste Disposal Method: Use approved Disposal method as recommended by state and local agencies.

SECTION VIII

Special Protection Information Respiratory Protection (Specify Type): Use appropriate NIOSH approved respiratory protection.

Ventilation: Local Exhaust Use sufficient local exhaust to control dust Mechanical Protective Gloves: Leather Gloves to avoid cuts from sharp edges. Eye Protection: Recommended for all industrial workplaces. Other Protective Equipment: Protective gloves for handling.

Section IX

Special Precautions Pre-cautions to be taken in handling and storing. The product should be stored in cool, dry, well-ventilated area, away from flammable materials or sources of heat and flame. Protect from temperature below -12 C or 10 F.

Appendices

This product is recyclable check with local authority for disposal

Roman 880 Clear Commercial Adhesive Approved

Cleaning surface solutions: Warm water on soft cloth | 75% Alcohol on soft cloth

Application varies based on surface substrate/s

Page 2 of 2 / End; MSDS

Intentionally left blank